Journal of Nonlinear Analysis and Optimization Vol. 13, Issue. 2 : 2022 ISSN : **1906-9685** 



# SERIAL LINKS BASED EMBEDDED TRANSITION INVERSION CODING WITH LOW SWITCHING ACTIVITY

#### R Arun Kumar, G Vijaya Bhai, Assistant Professor Department Of ECE Sree Chaitanya College of Engineering, Karimnagar

#### **ABSTRACT:**

The embedded transition inversion (ETI) is recommended for serializing parallel buses in order to reduce bit transitions. It is possible to reduce the assumed power even further. This research proposes an embedded transition inversion (ETI) coding technique that utilizes the phase difference between the clock and data in the delivered serial data to alleviate the extra indication bit problem. Pipelining is a technique used to minimize performance loss and optimize its implementation for use in real-world systems. As the data is being fed into the buffer, this is achieved by making the decision and encoding on the fly. Since most existing algorithms cannot be implemented with minimal latency, they lack this characteristic.

#### 1. INTRODUCTION

Advanced silicon technology offers the possibility of integrating hundreds of millions of transistors into a single chip, which makes system-on-chip (SoC) design possible. With the continuous scaling of silicon technology, area and power dissipation of interconnects are one of the main bottlenecks for both on-chip and off-chip buses. Multiplexing parallel buses into a serial link enables an improvement in terms of reducing interconnect area, coupling capacitance, and crosstalk, but it may increase the overall switching activity factor (AF) and energy dissipation. Therefore, an efficient coding method that reduces the switching AF is important issues in serial interconnect design. The embedded transition inversion (ETI) coding scheme reduce the switching activity factor and solve the extra bit indication of TIC coding scheme by embedding the inversion information in the phase difference between the clock and the encoded data.

When there is an inversion in the data word, a phase difference is generated between the clock and data. Otherwise, the data word remains unchanged and there is no phase difference between the clock and the data. Need of phase difference is decided by the decision bit. The decision bit is decided by the no. of transitions when the no. of transitions are more than half of the word length, every even bit of the data word will be inverted and then decision bit sets to high. This operation is performed at transmitted section.

The receiver side adopts a phase detector (PD) to detect whether the received data word has been encoded or not. Statistical analysis and experimental results show that the proposed coding scheme has low transitions for different kinds of data patterns. Low power design, in a system perspective, happens at all levels of the digital electronic system stack. It is being done from the lowermost device level design to the topmost software design. And there are the intermediate levels where a lot of effort is being expended to make systems run at low power. This scheme eliminates the need of sending an extra bit by embedding the inversion information in the phase difference between the clock and the encoded data. When there is an inversion in the data word, a phase difference is generated between the clock and data. Otherwise, the data word remains unchanged and there is no phase difference between the clock and the data. The receiver side adopts a phase detector (PD) to detect whether the received data word has been encoded or not. A significant improvement in the interconnect energy dissipation is achieved by applying different word lengths by degree of multiplexing. However, the power reduction decreases when the degree of multiplexing increases. The Modified Embedded Transition Inversion (ETI) Coding scheme reduces the power consumption using sequential element. Advanced silicon technology offers the possibility of integrating hundreds of millions of transistors into a single chip, which makes system-on-chip (SoC) design possible. With the continuous scaling of silicon technology, area and power dissipation of interconnects are one of the main bottlenecks for both on-chip and off-chip buses. Multiplexing parallel buses into a serial link enables an improvement in terms of reducing interconnect area, coupling capacitance, and crosstalk [1], but it may increase the overall switching activity factor (AF) and energy dissipation. Therefore, an efficient coding method that reduces the switching AF is an important issue in serial interconnect design. Many studies attempt to reduce the AF of parallel buses. For example, Stan and Burleson [2] introduced a bus-invert method that transmits the original or inverted pattern to minimize the switching activity. Researchers have proposed many techniques to improve the businvert coding method, such as the partial bus-invert coding [3] and weight-based businvert coding methods [4]. The schemes mentioned above use an extra channel to send the inversion indication signal. Kuo et al. [5] proposed the serial coding technique to solve the extra channel problem. They append extra information bits to the back of the original data word. Although this approach resolves the area overhead problem, it increases data latency. Three level differential encoding is proposed for parallel bus [6] to enable multiple drivers at the transmitter and to recycle the same current and reduce power consumption [6]. Joint crosstalk avoidance code and error correction code are proposed to reduce the power in parallel bus [7]. Huang et al. [8] further proposed combining serializing bus with the joint crosstalk avoidance code and error correction code to reduce the power. Serialized low-energy transmission (SILENT) [1] is a coding method used in reducing the switching activity for serial links. This approach encodes every single bit in the parallel bus using the XOR gate, and multiplexes the encoded parallel buses into a serial link. The XOR operation sets an adjacent bit with the same value to zero. The greater the correlation is, the more zeros the encoder produces. This method is designed for data with strong correlation. Bharghava et al. [9] proposed the transition inversion coding (TIC) technique to reduce switching activity for random data and to detect errors. Their technique counts the transitions in the data word, and inverts the transition states if the number of transitions in a data word is more than half of the word length. The scheme sets the current bit in the serial stream to be the same as the previous encoded bit when there is a transition. Otherwise, it is set to the inversion of the previous encoded bit. A transition indication bit is added in every data word. This extra bit not only increases the number of transmitted bits, but also increases the transitions and latency. Lee et al. [10]- [12] used serial links as communication channels on an on-chip network architecture for SoC. The serial links reduce the area of communication channels by 57% compared with a nonserialized approach [10]. This approach also reduces the switch activity because the coupling capacitance of the interconnect wires decreases [10]-[12]. Forward error correction (FEC) code is used to reduce the serial link power by trading off the FEC coding gain with specifications on transmit swing, analog-to-digital converter precision, jitter tolerance, receive amplification, and by enabling higher signal constellations [13]. By combining the single and differential signals and 8B/10B coding, a high speed phase tracking clock recovery is developed for serial link to reduce the power [14]. To utilize the relation between data in a link, the encoder reorders or shuffles the M bits in the parallel bus such that the encoded data are less correlated or silent [15]. Then the encoded data are serialized with one control bit. The silent coding with shuffling can reduce the power dissipation compared to the silent coding

#### 2. LITERATURE SURVEY

Parallel buses multiplexed into a serial link enables an improvement in terms of reducing interconnect area, coupling capacitance, and crosstalk, but it increases the overall switching activity factor (AF) and energy dissipation .Therefore, an efficient coding method needed to reduce the switching AF is an important issue in serial interconnect design. Many studies attempt to reduce the AF of parallel buses. Stan and Burleson introduced a bus-invert method that transmits the original or inverted pattern to minimize the switching activity. Researchers have proposed many techniques to improve the bus-invert coding method, such as the partial bus-invert coding and weight-based bus

invert coding methods. The schemes mentioned above use an extra channel to send the inversion indication signal. Kuo et al. proposed the serial coding technique to solve the extra channel problem. They append extra information bits to the back of the original data word. Although this approach resolves the area overhead problem, it increases data latency. Three level differential encoding is proposed for parallel bus to enable multiple drivers at the transmitter and to recycle the same current and reduce power consumption. Joint crosstalk avoidance code and error correction code are proposed to reduce the power in parallel bus. Huang et al. further proposed combining serializing bus with the joint crosstalk avoidance code and error correction code to reduce the power.

Serialized low-energy transmission (SILENT) is a coding method used in reducing the switching activity for serial links. This approach encodes every single bit in the parallel bus using the XOR gate, and multiplexes the encoded parallel buses into a serial link. The XOR operation sets an adjacent bit with the same value to zero. The greater the correlation is, the more zeros the encoder produces this method is designed for data with strong correlation. Bharghava et al. proposed the transition inversion coding (TIC) technique to reduce switching activity for random data and to detect errors. Their technique counts the transitions in the data word, and inverts the transition states if the number of transitions in a data word is more than half of the word length. The scheme sets the current bit in the serial stream to be the same as the previous encoded bit when there is a transition. Otherwise, it is set to the inversion of the previous encoded bit. A transition indication bit is added in every data word. This extra bit not only increases the number of transmitted bits, but also increases the transitions and latency. Serial links as communication channels on on-chip network architecture for SoC. The serial links reduce the area of communication channels by 57% compared with a non serialized approach. This approach also reduces the switch activity because the coupling capacitance of the interconnect wires. The embedded transition inversion (ETI) coding scheme is proposed to solve the extra bit indication. This scheme eliminates the need of sending an extra bit by embedding the inversion information in the phase difference between the clock and the encoded data. When there is an inversion in the data word, a phase difference is generated between the clock and data. Otherwise, the data word remains unchanged and there is no phase difference between the clock and the data. The improvement of transition reduction is 19% compared with that of the TIC. The receiver side adopts a phase detector (PD) to detect whether the received data word has been encoded or not.

#### 3. EXISTING SYSTEM TRANSITION INVERSION CODING



Bharghava proposed the transition inversion coding (TIC) technique to reduce switching activity for random data and to detect errors. Their technique counts the transitions in the data word, and inverts the transition states if the number of transitions in a data word is more than half of the word length. The scheme sets the current bit in the serial stream to be the same as the previous encoded bit when there is a transition. Otherwise, it is set to the inversion of the previous encoded bit. A transition indication bit is added in every data word. This extra bit not only increases the number of transmitted bits, but also increases the transitions and latency.

The embedded transition inversion coding (ETI) coding scheme to solve the TIC coding scheme issue of the extra indication bit [7]. The ETI scheme eliminates the need of sending an extra bit by embedding the inversion information in the phase difference between the clock and the encoded data. When there is an inversion in the data word, a phase difference is generated between the clock and data. Otherwise, the data word remains unchanged and there is no phase difference between the clock and the data. The improvement of transition reduction is 19% compared with that of the TIC. The receiver side adopts a phase detector (PD) to detect whether the received data word has been encoded or not.

### **DRAWBACKS:**

- 1. more area occupancy
- 2. More propagation delay
- 3. Un necessary glitters are produced
- 4. Low Throughput

# 4. **PROPOSED ARCHITECTURE:**

### **ETI ARCHITECTURE:**

The TIC is one of the methods developed for random data [9]. This method adds a transition indication bit to every data word to indicate if there is an inversion or not. This inversion coding is performed on every bit of two consecutive bits in the serial stream. The extra indication bit increases the switching activity .The ETI coding scheme that operates on a two-bit basis and removes all the transition indication bits. The architecture of ETI coding scheme shown in below Fig.3.3.

The ETI architecture mainly contains the four sections

- i) Serialization
- ii) ETI encoder
- iii) ETI decoder
- iv) Deserialization

Each serial link has m input bit streams that are multiplexed by a serializer, followed by the ETI encoding. The encoded stream is transmitted through the serial link and followed by the ETI decoding and a deserializer.



# Fig:1. ETI architecture Serialization:

Serial communication has many advantages over multi bit parallel communication in respects of signal skew, crosstalk, area cost, and wiring congestion. We propose multiplexing the data of bus lines onto one line (a serial link).

This converts the parallel –line bus into serial links, which reduces the number of physical bus lines, for the same bus area, this reduction in the number of bus lines leads to a larger interconnect width and pitch (area). The larger line pitch reduces the coupling capacitance, while the wider interconnects reduce the resistivity, leading to a significant improvement in the interconnect

energy dissipation and delay. The reduction in delay can be transformed into a further energy reduction by reducing the number and size of required repeaters. By carefully selecting the number of serial links in the bus, a significant improvement in the overall energy dissipation can be achieved. This improvement increases as technology scales.

Serialization with n/m ETI serial links with n input bit streams under degree of multiplexing m. Fig3.4. Each serial link has m input bit streams that are multiplexed by a serializer, followed by the ETI encoding The encoded stream is transmitted through the serial link and followed by the ETI decoding and a deserializer. The example for serializer is shown in Fig. 3.5.



Fig : 2. n/m serial links with n input bit streams under the degree of multiplexing m



ISim (P.20131013) - [Default.wcfg]																			-	٥	×
															- 6' X						
	<b>v</b>  /	(-= E+0 (24) ↓				- <b>*</b> * :	PPS				T T		P. 1.0	Jus 💟 🍕 I	691	Rendunch			2 000	500 pc	
Instances and Processes ++ L		Ubjects Simulation Objects fr	or toomodule	+		<b>*</b>													2,000,	300 p3	
						Nam	ne		Value			1,999,80	Q ps	[2,000,000 ps	2	,000,200 ps	2,000	,400 ps	2,000,	600 ps	2
Instance and Process Name	Desig		66/ 60		\$	8	la cik		1			HH		HHH	T						
topmodule	topmc	Object Name	Value			-	ip[7:0]		01011011		001	01110				000	1011011				
🎯 std_logic_1164	std_lo	🗓 clk	1		6		on[7:0]		01011011		00	101110		fvvev			0101	1011			
std_logic_arith	std_lo	> 📷 ip[7:0]	01011	011			E an										0101				
std_logic_unsigned	std_lo	⊳ 📸 op[7:0]	01011	011		2	10 UD				00.4							10			
		lla db	1		1	° 12.	C DZOP[/:		00001110		001	01110		<u>1º</u> /			000011	10			
	5	B20p[/:0]	00001.	110	1 =	èr 📃	le ones		0							°					
	1	lains	1		1.	• L	💩 ips	0	0												
	1	Ц ьо	1				😸 b0														
	-	ll b1	0		1		6 b1														
	8	⊳ 📸 b0b1[1:0]	10			°i 💌	😸 b0b1[1:	0]	10			10		) 11				10			
> 💑 qb[7:0]			10100	100		Fil 🕨	🕨 📑 qb[7:0]		10100100		11010001						10100100				
	1	Ixop[7:0]	00001	110			txop[7:0	D] (	00001110		00	101110		X X0X			0000	1110			ا تک
					1	ar a				2				$P^{\circ} - c$							
	5				1																
										X1:	2.000.600	ns									
<	>					1			7												2
AInstances an 🔒 Memory 📔 Sou	urce	<			>	201			Default	t.wcfg			×								
Console														-							+ 🗆 🗗 X
Fran 1.000s																					-
# isim force add {/topmodule/ip} 01011011 ·	-radix bin																				
ISim>																					
Frun 1.00us																					~
Console Compilation Log	Breako	oints 🐹 Find in	Files Results	Sear	ch Results																
																			Sim T	ime: 3,0	00,000 ps
			-		_	-				-		~	and the second s						1	3:19	_
P Type here to search			0	<b>P</b> t		0		×	-			9	ISIN			🐼 31°C	~ 4	上 (1)) EN	IG		

# ADVANTAGES

- i. Low latency
- ii. Low hardware over area head.
- iii. Less complexity

### APPLICATIONS

- i. Communications: Zigbee, Bluetooth
- ii. Biomedical: CRO with ECG
- iv. Computers: System with keypad, mouse

#### 6. CONCLUSION:

The ETI system reduces the extra bit used in the TIC technique, as well as crosstalk and energy dissipation. The phase difference between the data and clock is used by the ETI technique to identify the bit inversion. The proposed ETI methodology in this thesis minimizes power, time, and crosstalk in comparison to the current ETI method. The reduced latency and low power consumption of this upgraded approach make it more advantageous for multipurpose applications.

## **FUTURE SCOPE:**

The recommended hardware can be duplicated on an Application Specific Integrated Circuit (ASIC) when encoding techniques demand less space. Using the FPGA's parallelism and pipelining characteristics, many data compression techniques (Huffman, Lempel-Ziv, Arithmetic, and Shannon-Fano) can be separated from one another.

#### **References:**

[1]. Abinesh R., Bharghava R., Suresh Purini, Govindarajulu Regeti, "Transition Inversion based Low Power data coding scheme for Buffered Data Transfer", Accepted for publication in special issue of Journal of Low Power Electronics, October 2010.

[2] Abinesh R., Bharghava R., Suresh Purini, Govindarajulu Regeti, "Transition Inversion based Low Power data coding scheme for Buffered Data Transfer", 23rd International Conference on VLSI Design, January 2010

[3] Abinesh R., Bharghava R., M.B. Srinivas, "Transition Inversion Based Low Power Data Coding Scheme for Synchronous Serial Communication", is VLSI, pp.103-108, 2009 IEEE Computer Society Annual Symposium on VLSI, 2009

[4].http://www.intel.com/consumer/products/style/netbook.htm Net book vs. Laptop and Entry Level Desktops.

[5]. Net book design considerations by Texas Instruments. http://focus.ti.com/docs/solution/folders/print/581.html

[6]. Nano-cmos scaling problems and implications. Nano-CMOS Circuit and Physical Design, Ban P. Wong, Anurag Mittal, Yu Cao, and Greg Starr, John Wiley & Sons Inc.

[7] M. Ghoneima, Y. Ismail, M. Khellah, J. Tschanz, and V. De, "Serial-link

bus: A low-power on-chip bus architecture," IEEE Trans. Circuits Syst.

I, Reg. Papers, vol. 56, no. 9, pp. 2020–2032, Sep. 2009.

[8] B. Razavi, "Challenges in the design of high-speed clock and data recovery circuits," *IEEE Commun. Mag.*, vol. 40, no. 8, pp. 94–101,

Aug. 2002.

[9]. Dhiman, G. and Rosing, T. S. 2007. Dynamic voltage frequency scaling for multitasking systems using online learning. In Proceedings of the 2007 international Symposium on Low Power Electronics and Design (Portland, OR, USA, August 27 - 29, 2007). ISLPED '07. ACM, New York, NY, 207-212.

[10]. M. R. Stan, W. P. Burleson. Bus-Invert Coding for Low Power I/O, IEEE Transactions on Very Large Integration Systems, Vol. 3, No. 1, pp. 49-58, March 1995.